

In re Patent Application of:  
SMITH ET AL  
Serial No. 10/760,996  
Filed: 01/20/2004

---

In the Claims:

Claims 1-14 (cancelled)

15. (currently amended) ~~The method according to claim 13~~ A method of delivering span power by way of a plurality of telecommunication wireline segments to respective ones of a plurality of remote telecommunication terminals, said method comprising the steps of:

(a) coupling said plurality of telecommunication wireline segments to a span power bus, so that span power is coupled from said span power bus to said plurality of telecommunication wireline segments;

(b) coupling respective ones of said plurality of telecommunication wireline segments to respective ones of said plurality of remote telecommunication terminals, so that said span power is delivered by said plurality of telecommunication wireline segments to said respective ones of said plurality of remote telecommunication terminals;

(c) coupling respective ones of said plurality of telecommunication wireline segments to respective ones of a plurality of ground fault detection and isolation circuits, a respective ground fault being capable of causing electrical current in excess of normal load current to flow in a remote telecommunication terminal that is connected to the respective telecommunication wireline segment in which the ground fault has occurred, and causing a reduction in said span power to a level that prevents proper operation of a remote telecommunication terminal that is coupled to a telecommunication wireline segment in which no ground fault has occurred;

(d) causing said ground fault detection and isolation circuits to monitor said plurality of telecommunication wireline segments for the occurrence of a ground fault therein; and

(e) in response to a ground fault detection and isolation

In re Patent Application of:  
**SMITH ET AL**  
Serial No. 10/760,996  
Filed: 01/20/2004

---

circuit detecting, in step (d), the occurrence of a ground fault in an associated telecommunication wireline segment to which said ground fault detection and isolation circuit is coupled, causing said ground fault detection and isolation circuit to decouple and isolate said associated telecommunication wireline segment from said span power bus, so as to prevent said reduction in said span power being delivered by others of said plurality of telecommunication wireline segments, in which no ground fault has been detected as having occurred, to remote telecommunication terminals coupled thereto, thereby preventing misoperation of said remote telecommunication terminals coupled to said others of said plurality of telecommunication wireline segments, wherein  
step (d) comprises the steps of:

(d1) at said ground fault detection and isolation circuit, measuring a first parameter representative of current flowing in a first segment portion of said associated telecommunication wireline segment to said remote telecommunication terminal, and measuring a second parameter representative of current flowing in a second segment portion of said associated telecommunication wireline segment from said remote telecommunication terminal, and

(d2) at said ground fault detection and isolation circuit, in response a difference in said first and second parameters, providing an output representative of the occurrence of a ground fault in said associated telecommunication wireline segment, and wherein

step (e) comprises causing said ground fault detection and isolation circuit to decouple, and thereby isolate, said associated telecommunication wireline segment from said span power bus, in response to step (d1) providing said output representative of the occurrence of a ground fault in said associated telecommunication wireline segment.

16. (previously presented) The method according to claim 15, wherein step (d1) comprises coupling a first sense resistor in

In re Patent Application of:  
SMITH ET AL  
Serial No. 10/760,996  
Filed: 01/20/2004

---

said first segment portion of said associated telecommunication wireline segment and generating a first output voltage representative of current flowing in said first sense resistor, and coupling a second sense resistor in said second segment portion of said associated telecommunication wireline segment and generating a second output voltage representative of current flowing in said second sense resistor, and step (d2) comprises detecting a difference between said first and second output voltages, and generating said output representative of a ground fault in said associated telecommunication wireline segment, in response to a prescribed difference between said first and second output voltages.

17. (previously presented) The method according to claim 16, wherein step (d1) comprises coupling said first sense resistor to a current mirror that is operative to generate an output current in accordance with current flowing through said first sense resistor, and coupling said current mirror to a differential amplifier, which generates an output for controlling current through a controlled current device coupled in circuit with said current mirror and an output resistor across which said first output voltage is produced.

18. (previously presented) The method according to claim 17, wherein step (d1) further comprises coupling a voltage across said second sense resistor to a differential amplifier, which produces said second output voltage, and step (d2) comprises differentially combining said first and second output voltages to provide said output representative of a ground fault in said associated telecommunication wireline segment.

Claims 19-20 (cancelled)

21. (currently amended) ~~The method according to claim 19 A~~

In re Patent Application of:  
SMITH ET AL  
Serial No. 10/760,996  
Filed: 01/20/2004

---

method of delivering power, applied from an electrical power source to a span power bus, by way of a plurality of telecommunication wireline segments to respective ones of a plurality of remote telecommunication terminals, said method comprising the steps of:

(a) coupling first portions of said plurality of telecommunication wireline segments to said span power bus, so that power is coupled from said span power bus to said first portions of said plurality of telecommunication wireline segments;

(b) coupling second portions of said plurality of telecommunication wireline segments to said respective ones of said plurality of remote telecommunication terminals, so that power coupled from said span power bus to said first portions of said plurality of telecommunication wireline segments is delivered by said second portions of said plurality of telecommunication wireline segments to said respective ones of said plurality of remote telecommunication terminals;

(c) coupling the first and second portions of respective ones of said plurality of telecommunication wireline segments to respective ones of a plurality of ground fault detection and isolation circuits;

(d) causing each ground fault detection and isolation circuit to monitor the respective telecommunication wireline segment to which said each ground fault detection and isolation circuit is coupled for the occurrence of a ground fault; and

(e) in response to a respective ground fault detection and isolation circuit detecting the occurrence of a ground fault on said respective telecommunication wireline segment in step (d), causing said respective ground fault detection and isolation circuit to perform the operation of decoupling, and thereby isolating, said respective telecommunication wireline segment from said span power bus, said operation being effective to prevent a change in the power being delivered by others of said plurality of telecommunication wireline segments to remote telecommunication

In re Patent Application of:  
SMITH ET AL  
Serial No. 10/760,996  
Filed: 01/20/2004

---

terminals coupled thereto, and thereby prevent misoperation of said remote telecommunication terminals coupled to said others of said plurality of telecommunication wireline segments, wherein  
step (d) comprises the steps of:

(d1) at said each ground fault detection and isolation circuit, measuring a first parameter representative of current flowing in a first segment portion of said respective telecommunication wireline segment to said remote telecommunication terminal, and measuring a second parameter representative of current flowing in a second segment portion of said respective telecommunication wireline segment from said remote telecommunication terminal, and

(d2) at said each ground fault detection and isolation circuit, in response a difference in said first and second parameters, providing an output representative of the occurrence of a ground fault in said respective telecommunication wireline segment, and wherein

step (e) comprises causing said respective ground fault detection and isolation circuit to decouple, and thereby isolate, said respective telecommunication wireline segment from said span power bus, in response to step (d1) providing said output representative of the occurrence of a ground fault in said respective telecommunication wireline segment.

22. (previously presented) The method according to claim 21, wherein step (d1) comprises coupling a first sense resistor in said first segment portion of said respective telecommunication wireline segment and generating a first output voltage representative of current flowing in said first sense resistor, and coupling a second sense resistor in said second segment portion of said respective telecommunication wireline segment and generating a second output voltage representative of current flowing in said second sense resistor, and step (d2) comprises detecting a difference between said first and second output

In re Patent Application of:  
SMITH ET AL  
Serial No. 10/760,996  
Filed: 01/20/2004

---

voltages, and generating said output representative of a ground fault in said respective telecommunication wireline segment, in response to a prescribed difference between said first and second output voltages.

23. (previously presented) The method according to claim 22, wherein step (d1) comprises coupling said first sense resistor to a current mirror that is operative to generate an output current in accordance with current flowing through said first sense resistor, and coupling said current mirror to a differential amplifier, which generates an output for controlling current through a controlled current device coupled in circuit with said current mirror and an output resistor across which said first output voltage is produced.

24. (previously presented) The method according to claim 23, wherein step (d1) further comprises coupling a voltage across said second sense resistor to a differential amplifier, which produces said second output voltage, and step (d2) comprises differentially combining said first and second output voltages to provide said output representative of a ground fault in said respective telecommunication wireline segment.

Claims 25-26 (cancelled).

27. (currently amended) ~~The system according to claim 25~~ A system for controlling delivery of span power supplied by a span power bus to respective ones of a plurality of remote telecommunication terminals, said system comprising:

a plurality of telecommunication wireline segments coupled to said span power bus, so that span power is coupled from said span power bus to said plurality of telecommunication wireline segments, respective ones of said plurality of telecommunication wireline segments being coupled to respective ones of said

In re Patent Application of:  
SMITH ET AL  
Serial No. 10/760,996  
Filed: 01/20/2004

---

plurality of remote telecommunication terminals, so that said span power is delivered by said plurality of telecommunication wireline segments to said respective ones of said plurality of remote telecommunication terminals; and

a plurality of ground fault detection and isolation circuits, coupled with respective ones of said plurality of telecommunication wireline segments between said span power bus and said plurality of remote telecommunication terminals, and being operative to monitor respective ones of said plurality of telecommunication wireline segments for the occurrence of a ground fault therein, a ground fault being capable of presenting a hazardous voltage condition to service personnel, causing electrical current in excess of normal load current to flow in a remote telecommunication terminal that is connected to the respective telecommunication wireline segment in which the ground fault has occurred, as well as producing a reduction of normal span power supplied by said span power bus and said telecommunication wireline segments, causing remote telecommunication terminals to malfunction; and wherein

a respective ground fault detection and isolation circuit is operative, in response to detecting the occurrence of a ground fault in an associated telecommunication wireline segment to which said respective ground fault detection and isolation circuit is coupled, to decouple and isolate said associated telecommunication wireline segment from said span power bus, so as to prevent said reduction in said span power being delivered by others of said plurality of telecommunication wireline segments, in which no ground fault has been detected as having occurred, to remote telecommunication terminals coupled thereto, thereby preventing misoperation of said remote telecommunication terminals coupled to said others of said plurality of telecommunication wireline segments, wherein

said respective ground fault detection and isolation circuit is operative to detect the occurrence of a ground fault in said

In re Patent Application of:  
**SMITH ET AL**  
Serial No. 10/760,996  
Filed: 01/20/2004

---

associated telecommunication wireline segment and to decouple and isolate said associated telecommunication wireline segment from said span power bus by:

i- measuring a first parameter representative of current flowing in a first segment portion of said associated telecommunication wireline segment to said remote telecommunication terminal,

ii- measuring a second parameter representative of current flowing in a second segment portion of said associated telecommunication wireline segment from said remote telecommunication terminal, and

iii- in response to detecting a difference in said first and second parameters - indicating the occurrence of a ground fault - decoupling, and thereby isolating, said associated telecommunication wireline segment from said span power bus.

28. (previously presented) The system according to claim 27, wherein said respective ground fault detection and isolation circuit is operative to perform step i by coupling a first sense resistor in said first segment portion of said associated telecommunication wireline segment and generating a first output voltage representative of current flowing in said first sense resistor, is operative to perform step ii by coupling a second sense resistor in said second segment portion of said associated telecommunication wireline segment and generating a second output voltage representative of current flowing in said second sense resistor, and is operative to perform step iii by detecting a prescribed difference between said first and second output voltages - indicating the occurrence of a ground fault - and decoupling, and thereby isolating, said associated telecommunication wireline segment from said span power bus.

29. (previously presented) The system according to claim 28, wherein said respective ground fault detection and isolation



In re Patent Application of:  
**SMITH ET AL**  
Serial No. 10/760,996  
Filed: 01/20/2004

---

circuit is operative to perform step i by coupling said first sense resistor to a current mirror that is operative to generate an output current in accordance with current flowing through said first sense resistor, and coupling said current mirror to a differential amplifier, which generates an output for controlling current through a controlled current device coupled in circuit with said current mirror and an output resistor across which said first output voltage is produced, and coupling a voltage across said second sense resistor to a differential amplifier, which produces said second output voltage, is operative to perform step ii by differentially combining said first and second output voltages, and is operative to perform step iii by detecting a prescribed difference between said first and second output voltages - indicating the occurrence of a ground fault - and decoupling, and thereby isolating, said associated telecommunication wireline segment from said span power bus.